

BGAN terminals



Wideye Sabre

Explorer 100/110

Explorer 500

HNS 9201

Explorer 700

HNS 9250

Explorer 727

Manufacturer:

Addvalue Communications
www.wideye.com.sg

Thrane & Thrane
www.thrane.com

Thrane & Thrane
www.thrane.com

Hughes Network
www.hns.com

Thrane & Thrane
www.thrane.com

Hughes Network
www.hns.com

Thrane & Thrane
www.thrane.com

Size:

384 x 180mm (1.2 kgs)

200 x 140 mm (>1 kb)

217 x 217mm (<1.5 kg)

345 x 275 mm (2.8kg)

290 x 399mm (3.2kg)

Terminal: 27 x 34 x 5 cm
Antenna: 47 x 15 cm

Terminal: 42 x 247 x 270 mm
Antenna: 160 x 476mm

Standard IP:

Up to 384/240 kbps (receive/send)

Up to 384/240 kbps (receive/send)

Up to 464/448 kbps (receive/send)

Up to 492 (send & receive)

Up to 492 (send & receive)

Up to 492 (send & receive)

Up to 492 (send & receive)

Streaming IP:

32, 64 kbps (send & receive)

32, 64 kbps (send & receive)

32, 64, & 128 kbps (send & receive)

32, 64, 128 & 256 kbps (send & receive)

32, 64, 128 & 256 kbps (send & receive)

32, 64, 128 & 256 kbps (send & receive)

32, 64, 128 & 256 kbps (send & receive)

ISDN:

N/A

N/A

Via USB

1 x 64 kbps

2 x 64 kbps

1 x 64 kbps

1 x 64 kbps

Voice:

Via RJ11 or Bluetooth handset/headset

Via Thrane worldset, ISDN phones, Bluetooth handset

Via RJ11 or Bluetooth handset; 3.1 kHz audio

Via ISDN handset

Via RJ11 (x2) or Bluetooth handset; 3.1 kHz audio

Via ISDN handset

Via RJ11 (x2)

Data Interfaces:

USB, Bluetooth, Ethernet

USB, Bluetooth, Ethernet

USB Bluetooth, Ethernet

USB, Ethernet, WLAN 802.11 b

USB, Ethernet (x2), Bluetooth, WLAN 802.11 g, Digital I/O

USB, Ethernet, WLAN 802.11 b

Ethernet (x4), RJ11 (x2), Digital I/O

Ingress Protection:

IP 44

IP 44

IP 54

IP 55

IP 52 (transceiver)
IP 66 (antenna)

IP 56

IP 31 (terminal)
IP 56 (antenna)

